

**UL-16 *Spec37* Curved Vane
Racing Rotors Preferred by
Dirt Late Model &
Open Wheel Modified Racers**

*Lighter and stronger in track-tested,
race-winning Wilwood design*

- Proprietary *Spec37* iron alloy developed to withstand extreme temperatures with the highest degree of resistance against distortion, warping, cracking and wear
- True 11.75" diameter ensures proper pad sweep and maximum brake pad contact area
- 16 curved vane construction provides ultimate strength and enhanced airflow
- 1.00" rotor width eliminates the need for pad spacers with stock D-154 and original equipment replacement calipers
- Open-vane, minimal-obstruction design reduces the incidence of dirt and debris collection
- Lightweight design at only 6.9 pounds
- Available in HD plain face and GT asymmetrical slot pattern designs



UL-16HD



UL-16GT



ORDERING INFORMATION: Ultralite-16 Curved Vane *Spec37* Racing Rotors

DIAMETER	WIDTH	BOLT CIRCLE	HOLE TYPE	FAR SIDE I.D.	LUG I.D.	WEIGHT	STYLE	PART NUMBER
11.75"	1.00"	8 x 7.00"	.323"	8.46" (214,9)	6.38" (162,1)	6.9 lbs.	HD - R/H	160-15877
11.75"	1.00"	8 x 7.00"	.323"	8.46" (214,9)	6.38" (162,1)	6.9 lbs.	HD - L/H	160-15878
11.75"	1.00"	8 x 7.00"	.323"	8.46" (214,9)	6.38" (162,1)	6.9 lbs.	GT - R/H	160-15879
11.75"	1.00"	8 x 7.00"	.323"	8.46" (214,9)	6.38" (162,1)	6.9 lbs.	GT - L/H	160-15880